

A

09/26/97

J0494 U.S. PTO

# NEW UTILITY PATENT APPLICATION TRANSMITTAL (Small Entity)

(to be used for new applications only)

Docket No.  
30495.00.017

Total Pages in this Submission  
69

**TO THE ASSISTANT COMMISSIONER FOR PATENTS**  
**Washington, D.C. 20231**

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53 is a new utility patent application for an invention entitled:

**EXCAVATING TOOTH ASSEMBLY**

and invented by:

**Brian L. Launder; Charles Clendenning**

Enclosed are:

## Application Elements

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 49 pages and including the following:
  - ☒ Abstract of the Disclosure
  - ☒ Title of the Invention
  - ☐ Cross References to Related Applications (if applicable)
  - ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
  - ☐ Reference to Microfiche Appendix (if applicable)
  - ☒ Background of the Invention
  - ☒ Brief Summary of the Invention
  - ☒ Brief Description of the Drawings (if drawings filed)
  - ☒ Detailed Description
  - ☒ Claim(s) as Classified Below
3. ☒ Drawing(s) (when necessary as prescribed by 35 USC 113)
  - ☐ Formal ☒ Informal
  - Number of Sheets 10
4. ☒ Declaration
  - ☒ Executed ☐ Unexecuted ☒ With Power of Attorney ☐ Without Power of Attorney

**NEW UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Small Entity)**

*(to be used for new applications only)*

Docket No.  
30495.00.017

Total Pages in this Submission  
69

**Application Elements (Continued)**

5. ☐ Genetic Sequence Submission *(if applicable, all must be included)*
- ☐ Paper Copy
- ☐ Computer Readable Copy
- ☐ Statement Verifying Identical Paper and Computer Readable Copy

**Accompanying Application Parts**

6. ☐ Assignment Papers
7. ☐ Computer Program in Microfiche
8. ☐ Information Disclosure Statement/PTO-1449      ☐ Copies of IDS Citations
9. ☐ Petition
10. ☐ Preliminary Amendment
11. ☐ Proprietary Information
12. ☒ Acknowledgment postcard
13. ☒ Small Entity Statement(s) - Specify Number of Statements Submitted: 2
14. ☒ Certificate of Mailing
- ☐ First Class    ☒ Express Mail (Specify Label No.): EM143914082US
15. ☐ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*
16. ☐ English Translation Document *(if applicable)*

**NEW UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Small Entity)**

*(to be used for new applications only)*

Docket No.  
30495.00.017

Total Pages in this Submission  
69

**Accompanying Application Parts (Continued)**

17. ☐ Additional Enclosures *(please identify below):*


**Fee Calculation and Transmittal**

**CLAIMS AS FILED**

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	63	- 20 =	43	x \$11.00	\$473.00
Indep. Claims	13	- 3 =	10	x \$40.00	\$400.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$385.00
OTHER FEE <i>(specify purpose)</i>					\$0.00
TOTAL FILING FEE					\$1,258.00

- ☒ A check in the amount of \$1,258.00 to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 18-2284 as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of \_\_\_\_\_ as filing fee.
- ☐ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: September 26, 1997

  
Signature  
John W. Harbst, Reg. No. 28,018  
RUDNICK & WOLFE  
203 North LaSalle Street  
Chicago, IL 60601-1293

CC:

**NEW UTILITY PATENT APPLICATION TRANSMITTAL  
(Small Entity)**

*(to be used for new applications only)*

Docket No.  
30495.00.017

Total Pages in this Submission  
69

**TO THE ASSISTANT COMMISSIONER FOR PATENTS**  
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53 is a new utility patent application for an invention entitled:

**EXCAVATING TOOTH ASSEMBLY**

and invented by:

**Brian L. Launder; Charles Clendenning**

Enclosed are:

**Application Elements**

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 49 pages and including the following:
  - ☒ Abstract of the Disclosure
  - ☒ Title of the Invention
  - ☐ Cross References to Related Applications *(if applicable)*
  - ☐ Statement Regarding Federally-sponsored Research/Development *(if applicable)*
  - ☐ Reference to Microfiche Appendix *(if applicable)*
  - ☒ Background of the Invention
  - ☒ Brief Summary of the Invention
  - ☒ Brief Description of the Drawings *(if drawings filed)*
  - ☒ Detailed Description
  - ☒ Claim(s) as Classified Below
3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
  - ☐ Formal ☒ Informal
  - Number of Sheets 10
4. ☒ Declaration
  - ☒ Executed ☐ Unexecuted ☒ With Power of Attorney ☐ Without Power of Attorney

**NEW UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Small Entity)**

*(to be used for new applications only)*

Docket No.  
30495.00.017

Total Pages in this Submission  
69

**Application Elements (Continued)**

5. ☐ Genetic Sequence Submission *(if applicable, all must be included)*
- ☐ Paper Copy
- ☐ Computer Readable Copy
- ☐ Statement Verifying Identical Paper and Computer Readable Copy

**Accompanying Application Parts**

6. ☐ Assignment Papers
7. ☐ Computer Program in Microfiche
8. ☐ Information Disclosure Statement/PTO-1449    ☐ Copies of IDS Citations
9. ☐ Petition
10. ☐ Preliminary Amendment
11. ☐ Proprietary Information
12. ☒ Acknowledgment postcard
13. ☒ Small Entity Statement(s) - Specify Number of Statements Submitted: 2
14. ☒ Certificate of Mailing
- ☐ First Class    ☒ Express Mail (Specify Label No.): EM143914082US
15. ☐ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*
16. ☐ English Translation Document *(if applicable)*

**NEW UTILITY PATENT APPLICATION TRANSMITTAL**  
**(Small Entity)**

*(to be used for new applications only)*

Docket No.  
30495.00.017

Total Pages in this Submission  
69

**Accompanying Application Parts (Continued)**

17. ☐ Additional Enclosures (please identify below):


**Fee Calculation and Transmittal**

**CLAIMS AS FILED**

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	63	- 20 =	43	x \$11.00	\$473.00
Indep. Claims	13	- 3 =	10	x \$40.00	\$400.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$385.00
OTHER FEE (specify purpose) _____					\$0.00
TOTAL FILING FEE					\$1,258.00

- ☒ A check in the amount of **\$1,258.00** to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. **18-2284** as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of \_\_\_\_\_ as filing fee.
- ☐ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: September 26, 1997

  
Signature

John W. Harbst, Reg. No. 28,018  
RUDNICK & WOLFE  
203 North LaSalle Street  
Chicago, IL 60601-1293

CC:

"Express Mail" mailing label number

EM143914082US

Date of Deposit September 26, 1997

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR § 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

John W. Harbst

(Typed or printed name of person mailing paper or fee)



(Signature of person mailing paper or fee)

**PATENT**

Docket No. 30495.00.017

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTOR:

Brian L. Launder  
Charles Clendenning

TITLE:

EXCAVATING TOOTH ASSEMBLY

ATTORNEY:

John W. Harbst

RUDNICK & WOLFE  
203 North LaSalle Street  
Chicago, Illinois 60601  
(312) 368-4000

269260" 60682680

## EXCAVATING TOOTH ASSEMBLY

### FIELD OF THE INVENTION

5 The present invention relates generally to an excavating tooth assembly for a shovel or dipper bucket of large excavating equipment, and more particularly, to a mating configuration of an adapter and an excavating tooth which improves the bearing surfaces for absorbing vertical loads and inhibits lateral movement of the excavating tooth with respect to the adapter during use.

### BACKGROUND OF THE INVENTION

10 Earthworking tools such as excavating teeth are commonly known in the industry for use in conjunction with earthmoving implements such as shovels or dipper buckets. Typically, such teeth are mounted on spaced apart adapters or nose pieces of the implement to facilitate repair and, when necessary, replacement of the teeth should they become broken or dull. Periodic replacement is often necessary since the tools are subject to extreme loads and wear due to operating conditions where they encounter rock, sand and other types of abrasive earthen materials.

15 The adapters are generally configured with a nose portion having a triangular or tapered portion when viewed in longitudinal section. The excavating teeth are also provided with a generally triangular or tapered cavity or hollow for a mating fit with the nose portion of the adapters. To secure the excavating tooth to the adapter, and to allow for replacement of the tooth, a removable fastener such as a retaining pin is typically inserted through opposing holes in the excavating tooth and through a bore in the adapter.

20 As will be appreciated by those skilled in the art, the bore is formed in the adapter and



the opposing holes are formed in the excavating tooth with exacting accuracy and preciseness to assure an appropriate and mating fit between the parts. As will be appreciated, an error in placement of the bore in the adapter or the opposing holes in the digging tooth can result in poor mating between confronting surfaces on the tooth and the adapter. Such misfittings can cause significant problems resulting in undue wear between the component parts during operation of the digging or excavating tooth assembly.

In response to the tremendous forces exerted on the digging tooth during excavation, the tooth tends to move laterally, vertically or rotationally relative to the adapter, thereby causing undesirable wear on the respective parts. Moreover, during an excavating operation tremendous forces are placed on the removable fastener used to hold the excavating teeth on to their respective adapter. As a result of the forces acting on the tooth, the pin often becomes loose and fails to operably hold the tooth onto the adapter. Accordingly, the tooth separates from the adapter causing additional problems during the excavating operation.

Thus, there is a continuing need and desire for an excavating tooth assembly which is configured to optimize distribution of forces between the components thereof and prevent undesirable movement therebetween in order to minimize the frequency with which the parts must be replaced, thereby reducing the overall number of replacement parts and the time required to perform the replacement operations. Also, there continues to be a need and a desire for an excavating tooth assembly which is specifically designed to enhance the holding ability of the removable retainer thereby inhibiting inadvertent separation and loss of the excavating tooth relative to the adapter.

## SUMMARY OF THE INVENTION

In view of the above, and in accordance with the present invention, there is provided an excavating tooth assembly including an adapter and an excavating tooth. To promote its repair and, if necessary, replacement, a fastener maintains the excavating tooth in operable relationship with and releasably connected to the adapter. The excavating tooth preferably has a hollow mounting end defining a cavity configured to mate with a nose portion of the adapter. The hollow mounting end of the tooth includes inner tapered surfaces adapted to mate with outer tapered surfaces on the nose portion of the adapter.

In one aspect of the invention, the outer tapered surfaces of the adapter are each configured with a pair of fore-and-aft spaced stabilizing land sections. Each stabilizing land section on the nose portion of the adapter defines a flat surface extending generally parallel to the centerline of the adapter. Additionally, each stabilizing land section on the adapter has a substantially vertical stabilizing wall extending thereabout for advantageously transmitting forces acting on the tooth assembly toward a centerline of the adapter thereby enhancing performance characteristics of the tooth assembly.

The inner tapered surfaces at the hollow mounting end of the tooth has a configuration complementary to that of the outer surface on the adapter. That is, the inner tapered surfaces at the hollow mounting end of the excavating tooth each have a pair of fore-and-aft spaced stabilizing lands or transmitting sections. Each stabilizing land on the tooth likewise defines a flat extending generally parallel to the longitudinal axis of the tooth and sized relative to the lands on the adapter to readily and easily allow the tooth assembly to slidably fit endwise over and about the adapter. As will be appreciated, the rearmost stabilizing land or transmitting

section on the tooth is adapted to mate with the rearmost stabilizing land section on the adapter while the foremost flat or transmitting section on the tooth is adapted to mate with the foremost land section on the adapter.

In a preferred form of the invention, each stabilizing land on the adapter and excavating tooth further includes a substantially vertical wall expending from the flat defined by the respective stabilizing land. The generally vertical stabilizing walls of the stabilizing lands on the tooth are configured to mate with the corresponding stabilizing walls on the respective land sections on the adapter to facilitate transmission of forces between the excavating tooth and the adapter during operation of the excavating tooth assembly.

In another aspect of the invention, a bore extends through the rearward land section of the adapter, and a hole extends through the rearward stabilizing lands or transmitting sections of the tooth to act in conjunction with the bore for the insertion of a fastener therethrough to secure the tooth to the adapter. As will be appreciated, providing a generally horizontal flat on the adapter facilitates location and fabrication of the bore by inhibiting the tool used to make the bore from "dancing" along the angled surface of the adapter. That is, the flats defined by the rear stabilizing lands of the adapter are each intersected by and generally surround the centerline of the bore extending through the adapter for accommodating the fastener used to releasably interconnect the excavating tooth to the adapter. Thus, fabrication costs are reduced and the accuracy of the bore dimensions can be more precisely controlled.

In a preferred form of the invention, the generally vertical stabilizing walls of the land sections on the adapter and excavating tooth have complementary shapes to promote the transfer of forces acting on the tooth to the adapter and, thus, to the implement, thereby significantly

aiding in the distribution of the relatively large forces acting on the excavating teeth. To further facilitate the transmission of lateral forces acting on the tooth, a forward end portion of the adapter is bowed outwardly and a forward end portion of the cavity in the tooth is a corresponding concave shape for matingly receiving said nose piece.

5           The present invention provides significant advantages over other excavating tooth assemblies. By providing multiple horizontal and vertical stabilizing surfaces which mate in abutting relationship, especially in the vicinity of the bore in the adapter and the holes in the tooth, the transmission of vertical and horizontal forces from the excavating tooth to the adapter is optimized. As will be appreciated by those skilled in the art, the ability to effectively transfer forces between the adapter and the excavating tooth furthermore reduces wear between the component parts of the tooth assembly thus resulting in costs savings for replacement parts and labor.

10           According to another aspect of the present invention, elastomeric material is disposed between the adapter and the tooth to inhibit movement between the component parts of the tooth assembly thereby blunting the transference of forces between the tooth and the adapter and, thus, prolonging the usefulness of the engaging surfaces on the digging tooth assembly. In one form of the invention, an elastomeric spring is provided between the forward end portion of the adapter and the internal wall defined by the cavity in the tooth for continually urging the mating surfaces defined on the excavating tooth and the adapter into positive engagement relative to each other. Besides acting to blunt endwise impact forces between the tooth and the adapter, this elastomeric material furthermore augments the holding ability of the fastener extending through the tooth and the adapter. In another form of the invention, elastomeric material is

arranged along, and preferably about the adapter to resiliently fill tolerance voids and gaps between the components of the tooth assembly thereby blunting the impact forces inherent between such components during operation of the tooth assembly.

The present invention, together with further objects and advantages, will be best understood by reference to the following detailed description taken in conjunction with the accompanying drawings.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

FIGURE 1 is a longitudinal sectional view of one form of a multipiece excavating tooth assembly according to the present invention;

FIGURE 2 is a sectional view taken along line 2 - 2 of FIGURE 1;

FIGURE 3 is a longitudinal sectional view similar to FIGURE 1 but showing components of the multipiece excavating tooth assembly of the present invention in axially separated relation relative to each other;

FIGURE 4 is a perspective view of an adapter forming part of the excavating tooth assembly;

FIGURE 5 is a longitudinal sectional view similar to FIGURE 1 showing an alternative form of a multipiece excavating tooth assembly including elastomeric material disposed between components of the tooth assembly;

FIGURE 6 is a sectional view taken along line 6 - 6 of FIGURE 5;

FIGURE 7 is a sectional view similar to FIGURE 6 but showing an alternative form of elastomeric material disposed between components of the excavating tooth assembly;

FIGURE 8 is a longitudinal sectional view similar to FIGURE 1 showing another alternative form of a multipiece excavating tooth assembly including elastomeric material disposed between components of the tooth assembly;

FIGURE 9 is a longitudinal sectional view similar to FIGURE 1 showing still another alternative form of a multipiece excavating tooth assembly including elastomeric material disposed between components of the tooth assembly; and

FIGURE 10 is a sectional view taken along line 10 - 10 of FIGURE 9.

#### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

While the present invention is susceptible of embodiments in various forms, there is shown in the drawings and will hereinafter be described a preferred embodiment of the invention with the understanding that the present disclosure is to be considered as setting forth an exemplification of the invention which is not intended to limit the invention to the specific embodiment illustrated.

Referring now to the drawings, wherein like reference numerals refer to like parts throughout the several views, there is shown in FIGURE 1 an excavating tooth assembly including an adapter or support 12 and an excavating tooth 14. An elongated fastener 16 releasably interconnects and maintains the adapter 12 and tooth 14 in operating relationship relative to each other.

Although only a single tooth assembly 10 is shown in FIGURE 1 as being attached to an excavating implement 18 such as a forward lip 20 of a bucket or the like, it will be understood by those skilled in the art that on typical excavating equipment, a plurality of spaced apart tooth

assemblies, substantially identical to the tooth assembly 10, would extend from the bucket lip 20. Moreover, and as used herein, the terms horizontal and vertical refer generally to the orientation of the excavating implement or equipment when disposed on the ground, and wherein the excavating movement of the bucket 18 would be primarily in the vertical direction, although horizontal loads and forces are also imparted on the tooth assembly 10 during a normal excavating operation.

As illustrated in FIGURES 1 and 4, the adapter or support 12 has an elongated configuration defining a longitudinal centerline 21. The adapter or support 12 includes a conventional base portion 22 and a axially aligned nose portion 23 extending forwardly from and preferably formed integral with the base portion 22. The base portion 22 is preferably configured for releasable securement, as by a conventional wedge locking mechanism (not shown), to the forward lip 20 of the shovel or dipper bucket 18 of the earth excavation apparatus. As is conventional, the excavating tooth 14 fits endwise along and about the nose portion 23 of the adapter.

As shown, the nose portion 23 of the adapter or support 12 has a forwardly tapered configuration including angularly converging top and bottom exterior surfaces 24 and 26, respectively, for mating with and carrying the tooth 14. The nose portion 23 of the adapter or support 12 further includes laterally spaced side walls 28 and 30 (FIGURES 2 and 4). In the preferred form of the invention, the laterally spaced side walls 28, 30 likewise have a slight forwardly tapering slant thereto in the longitudinal direction thereof. Otherwise, the side walls 28, 30 each have a vertical orientation and are generally parallel to each other.

In the embodiment of the invention illustrated in FIGURES 11, 2 and 4, a terminal end

region 31 of the nose portion 23 of the adapter 12 defines a pair of laterally slanted surfaces 32 and 34 that laterally and angularly diverge away from the centerline 21 of the adapter 12. In the illustrated form of the invention, and to facilitate fabrication of the adapter 12, the terminal end portion 31 of the adapter 12 defines an outwardly bowed, curved terminal end portion. As will be appreciated, the laterally curved configuration at the terminal end 31 of the adapter 12 provides surfaces which, when a line is drawn tangential thereto, form an acute or diverging angle relative to the longitudinal centerline 21 of the adapter 12.

Moreover, in a preferred form of the invention, the free or terminal end portion 31 of the adapter 12 is provided with an upper radius 33 and a lower radius 35 at the juncture of the upper and lower surfaces 24 and 26, respectively. This configuration of the distal end of the adapter 12 assists in stabilizing the tooth 14 and provides a self-centering feature when the tooth 14 is under horizontal side loads.

The exterior slanted surfaces 24 and 26 on the support or adapter 12 each have recessed areas 40 arranged toward a distal end of the adapter 12. Preferably, the recessed areas 40 are equally disposed on the surfaces 24 and 26 and relative to the longitudinal centerline 21 of the adapter 12. Each recessed area 40 defines a flat substantially horizontal stabilizing surface or forward land 42 on the adapter 12.

Each land 42 protrudes inwardly from the respective slanted surfaces 24, 26 on the adapter 12 to define a generally flat or horizontal surface 43 extending generally parallel to the axis 21 of the adapter 12. As will be appreciated, a predetermined vertical distance is measurable between the flat or generally horizontal surfaces 43 of the lands 42 on the surfaces 24, 26 of the adapter 12. Moreover, each forward land 42 is bordered by a curvilinear and



generally vertical stabilizing wall 44. As will be described below, the horizontal forward lands 42 provide greater load distribution to absorb extreme vertical loads imparted to the tooth assembly during operation while the vertical stabilizing walls 44 provide additional vertical bearing surfaces to assist in absorbing extreme horizontal loads imparted to the tooth assembly 10 during an excavating operation.

As is conventional in multipiece tooth assemblies, the adapter 12 is further provided with a bore 46 for accommodating endwise passage of the fastener 16 therethrough thereby permitting the tooth 14 to be releasably maintained in operable association with the support or adapter 12. In the illustrated form of the invention, bore 46 defines an axis 48 extending vertically through a rearward portion of the tapered extension 23 of adapter 12 and opens to the tapered surfaces 24 and 26. As will be appreciated by those skilled in the art, the bore 46 accommodates endwise passage of the fastener 16 through the adapter or support 12. The bore 46 is suitably formed in the adapter 12 preferably using a drill but a punch may also be used in some circumstances.

The adapter 12 further defines a pair of flat substantially horizontal stabilizing surfaces or rearward lands 52 on the slanted surfaces 24 and 26 of the support 12 in surrounding relation relative to the axis 48 of the bore 46. As shown in FIGURE 1, the lands 52 are equally disposed on the surfaces 24 and 26 and relative to the longitudinal axis 21 of the adapter 12. Each land 52 protrudes outwardly from the respective slanted surface 24, 26 of the adapter 12 to define a generally horizontal or flat surface 53 extending generally parallel to the axis 21 of the adapter 12. A predetermined vertical distance is measurable between the flat or generally horizontal surfaces 53 defined by the lands 52 on the surfaces 24, 26 of the adapter 12.

As with the forward lands 42, the rearward lands 52 define curvilinear vertical stabilizing walls 54 extending thereabout. The walls 54 provide additional vertical bearing surfaces to assist in absorbing extreme horizontal loading imparted to the tooth assembly 10. In particular, side load distribution is transferred from horizontal to vertical in the areas of the adapter 12 surrounding the bore 46. The rearward lands 52 also provide greater vertical load distribution to absorb extreme vertical loads. Thus, the combination of the forward and rearward lands 42 and 52 substantially increases the stability of the tooth assembly 10 over a vast range of forces acting thereon during operation of the tooth assembly 10. Moreover, the additional material provided by the rearward lands 52 strengthens the area of the adapter surrounding the bore 46, which is typically the weakest area of the adapter 22.

It will be appreciated that although the terminal end portion 31 and the vertical stabilizing walls 44, 54 of the adapter 12 are preferably curvilinear, they could define other shapes capable of absorbing horizontal loads acting on the adapter 12. For example, the terminal end portion 31 and vertical stabilizing walls 44, 54 could each be configured with a V-shape since both sides of the "V" are eschewed or divergent from the centerline 21 of the adapter 12.

When the excavating tooth 10 is assembled, the excavating tooth 14 is configured for endwise accommodation along and about a lengthwise portion of the nose portion 23 of the adapter 12. As shown in FIGURE 1, the excavating tooth 14 has an elongated configuration defining a longitudinal axis 61 and with a lateral cutting edge 62 extending generally transverse to axis 61 disposed at one end thereof and a hollow mounting end 63 disposed at an opposite end thereof for allowing the tooth 14 to be mounted endwise onto the adapter 12.

As shown, the tooth 14 includes upper and lower exterior surfaces 64 and 66,

respectively, extending rearwardly from the cutting edge 62 and extend toward the rear end 63 of the tooth 14. As the surfaces 64, 66 extend rearwardly from the edge 62, they angularly diverge away from each other. In the illustrated form of the invention, the upper and lower surfaces 64, 66 on the tooth 14 preferably have substantially corresponding radii. Moreover, and as shown in FIGURE 2, the tooth 14 has a pair of laterally spaced side walls 68 and 70 which have a slightly tapering longitudinal configuration and which extend vertically and generally parallel relative to each other between the upper and lower surfaces 64 and 66, respectively, of the tooth 14.

As is conventional in multipiece tooth assemblies, the tooth 14 defines a blind cavity 70 opening to the rear end 63 of the tooth 14. The shape of the cavity 72 generally corresponds in configuration to the tapered extension 23 of the adapter 12 so that the tooth 14 can fit endwise thereon in mating relationship relative to the adapter 12. In a preferred form, the edge of the cavity 72 defined by the tooth 14 has an inwardly directed radius 73 extending thereabout to facilitate and guide endwise insertion of the nose portion 23 of the adapter 12 into a mating relationship or fit with the tooth 14.

As illustrated in FIGURES 1 and 3, the cavity 72 defined by tooth 14 includes upper and lower interior surfaces 74 and 76, respectively, extending forwardly from the open rear end of the cavity 72 toward the forward edge 62 (FIGURE 1) of the tooth 14 and converging toward each other at substantially the same angle that the exterior surfaces 24 and 26 are disposed on the nose region 23 of the adapter 12. As shown in FIGURE 2, a pair of generally vertical interior side walls 78 and 80 further serve to define the cavity 70. As will be appreciated, the interior side walls 78 and 80 of cavity 70 are configured to accommodate and mate with the

exterior side walls 28 and 30, respectively, on the nose region of the adapter 12.

In the embodiment of the invention illustrated in FIGURES 2 and 3, the interior slanted surfaces 74 and 76 of cavity 72 converge toward each other and terminate in an end wall 81 defining a pair of laterally slanted surfaces 82 and 84. The laterally slanted surfaces 82 and 84 angularly diverge away from the centerline 61 of the tooth 14. In the preferred form of the invention, and as shown in FIGURES 2, the laterally slanted surfaces 82, 84 defined by end wall 81 generally parallel the laterally slanted surfaces 32 and 34 defined at the terminal end portion 31 of adapter 12. In a most preferred form of the invention, and to facilitate fabrication of the cavity 32 defined by tooth 14, the terminal end wall 81 of cavity 72 defines a concavely bowed surface that generally parallels the bowed surface at the terminal end portion 31 of the nose portion of adapter 12.

As illustrated in FIGURE 3, the interior slanted surfaces 74 and 76 of cavity 72 have recessed areas 90 arranged toward the open end of the cavity 72 defined by tooth 14. The recessed areas 90 define rear stabilizing lands 92 disposed on the surfaces 74 and 76 of cavity 72 so as to mate with the pair of rearward stabilizing lands 52 on the nose portion 23 of the adapter 12.

In the illustrated form of the invention, the stabilizing lands 92 are equally disposed on the surfaces 74 and 76 and relative to the longitudinal axis 61 of the tooth 14. Each stabilizing land 92 protrudes inwardly from the respectively slanted surface 74, 76 of cavity 72 on the tooth 14 to define a generally flat or horizontal surface 93 extending generally parallel to the axis or longitudinal centerline 61 of the tooth 12. A predetermined vertical distance equal to or somewhat greater than the vertical distance between the rearward lands 52 on the adapter 12

separates the generally parallel surfaces 93 defined on the interior surfaces 74 and 76 of the cavity 72 defined by tooth 14. Additionally, each flat or horizontal surface 93 is bordered by a curvilinear generally vertical stabilizing wall 94. Suffice it to say, the stabilizing wall 94 has a configuration which complements and generally corresponds to the stabilizing wall 54 arranged in surrounding relation relative to the rearward lands 52 defined on the nose portion 23 of adapter 12.

The slanted upper and lower interior surfaces 74, 76 defined by cavity 72 of tooth 14 furthermore include a pair of forward stabilizing lands 102 arranged toward and rearwardly extending from the terminal wall 81 of the cavity 72. The stabilizing lands 102 are disposed on the surfaces 74 and 76 of cavity 72 so as to mate with the pair of forward lands 42 on the nose portion 23 of the adapter 12.

In the illustrated form of the invention, the stabilizing lands 102 protrude from the slanted surfaces 74, 76 of cavity 72 and are equally disposed on the surfaces 74, 76 and relative to the longitudinal axis 61 of the tooth 14. Each stabilizing land 102 defines a generally flat or horizontal surface 103 extending generally parallel to the longitudinal axis or center line 61 of the tooth 14. A predetermined vertical distance equal to or somewhat greater than the predetermined vertical distance between the forward lands 41 on the adapter 12 separates the generally parallel surfaces 103 defined on the interior slanted surfaces 74, 76 of the cavity 72 defined by tooth 14. By this design, the tooth 14 can be endwise fitted along and about a lengthwise portion of the nose portion 23 of the adapter 12 without the various pairs of stabilizing surfaces on the adapter 12 and tooth 14 interfering with each other during assembly of the tooth assembly 10.

Additionally, each stabilizing land 102 is bordered by a curvilinear and generally vertical stabilizing wall 104. Suffice it to say, the stabilizing wall 104 of stabilizing land 102 has a configuration which compliments and generally corresponds to the stabilizing wall 44 arranged in surrounding relation relative to the pair of forward lands 42 on the nose portion 23 of the adapter 12. As will be appreciated by those skilled in the art, if other configurations of the stabilizing walls 44, 54 or 94, 104 were provided on the adapter 12 or tooth 14, the complimentary or associated surface on the mating component of the tooth assembly 10 would be correspondingly shaped to mate therewith.

The tooth 14 further defines a pair of axially aligned holes or openings 106 and 108 for accommodating endwise passage of the fastener 16 therethrough thereby permitting the tooth 14 to be releasably attached and maintained in operable connection with the adapter 12. The relationship of the openings 106, 108 relative to the bore 46 in the adapter 14 is important to maintain the fastener 16 in operable relation with the tooth assembly during excavating operations. In the illustrative form of the invention, and because of the preferred disposition of bore 46 defined by adapter 12, the holes or openings 106, 108 are arranged in general vertical relationship relative to each other.

The fastener 16 for releasably interconnecting and maintaining the adapter 12 in tooth 14 in operable relation relative to each other can take many forms. In the illustrated embodiment, the fastener 16 is preferably of the type disclosed in co-pending and co-assigned United States Patent Application Serial No. 08/689,230 filed August 5, 1996; the full disclosure of which is incorporated herein by reference.

As shown in FIGURE 1, fastener 16 preferably comprises an elongated insert 112 and

10749192096-01\_7/15/97 10:00 AM

17

a retaining pin 114. The insert 112 includes a rigid elongated cylindrical sleeve 118 surrounded by a resilient member 120. Sleeve 118 is preferably fabricated from steel or the like and defines an internal bore 119 which opens to opposite ends of the sleeve 118. As shown in FIGURE 1, the insert 112 has a length generally equal to the predetermined distance separating the flats 53 defined by the stabilizing lands 52 on the slanted surfaces 24 and 26 of the nose portion 23 of adapter 12. Preferably, the resilient member 120 surrounds about a 270° circumferential portion of the sleeve 18 such that a portion of the sleeve is preferably free of resilient material before the insert 112 is inserted into combination with the adapter 12. Such design provides for compression relief for the insert 112 when inserted into the bore 46 of the adapter 12 and retaining pin 14 is inserted therethrough. Preferably, the outside diameter of the insert 112 is slightly greater than the diameter of the bore 46 and the adapter 12 so that the insert 112 is a light drive-in fit into the bore 46 of the adapter 12. A locking mechanism 122 including locking member 123 embedded in the resilient member 120 of insert 112 is disposed along the length of the insert 112 for releasably maintaining the retaining pin 114 in operable association therewith.

The retaining pin 114 of fastener 16 is preferably formed from solid steel and has a length greater than that of insert 112. The outside diameter of pin 114 is slightly less than the diameter of the axially aligned holes 106, 108 defined in the tooth 14. In the illustrated embodiment, opposite ends of pin 114 are chamfered to facilitate insertion of pin 114 into the insert 112. In the embodiment illustrated in FIGURE 1, pin 114 defines an annular channel or recess 124 which combines with the locking member 123 of locking mechanism 122 to releasably hold the retaining pin 114 in operable relation to insert 112.

To assemble the excavating tooth assembly 10, tooth 14 is placed endwise along and about a lengthwise portion of the tapered nose portion 23 of adapter 12 such that the opposed holes 106, 108 in the tooth 14 generally align with the bore 46 in the adapter 12. The retaining pin 114 is then inserted through either opening 106, 108 and through the insert 112. As the retaining pin 114 moves endwise through the insert 112, tooth 14 is biased rearwardly along the adapter 12 thereby maintaining a tight fit between tooth 14 and the adapter 12. Preferably, the openings or holes 106, 108 defined in the tooth 14 are intentionally offset or misaligned in a four-and-aft direction relative to the bore 46 defined in adapter 12 to provide the desired biasing effect. Moreover, the resilient member 120 serves to bias retaining pin 114 in the desired rearward direction. As shown in FIGURE 1, the effect of these biasing features is to force the retaining pin 114 against the rear portion of the holes 106, 108 defined by tooth 14. Moreover, when the annular channel or recess 124 on retaining pin 114 passes the locking mechanism 122, the locking member 123 automatically snaps into snug locking relationship with the pin 114 under the influence of the resilient member 120 thereby fixedly holding the retaining pin 114 in place relative to the insert 112. During operation of the excavating tooth assembly 10, the resilient member 120 holds the lock-in member 123 tight against the retaining pin such that the pin 114 is inhibited from endwise travel and through the holes 106, 108 defined by tooth 14.

When the tooth 14 is assembled on to the adapter 12, tooth 14 is prevented from rotating about either axes 21 or 61 by the fastener 16. Moreover, when the excavating tooth assembly 10 is assembled, the four-and-aft spaced pairs of cooperating stabilizing lands 42, 102 and 52, 92 defined on the adapter 12 in excavating tooth 14 furthermore minimize movement of the component parts of the tooth assembly relative to each other. More specifically, the generally



flat surfaces 43 on the forward stabilizing lands of the adapter 12 are disposed in dimensioned to be arranged in operable relationship with the flat surfaces 103 and the forward stabilizing lands 102 of tooth 14. Similarly, the generally flat or horizontal surfaces 53 of the rear stabilizing lands 52 on the adapter 12 are disposed in dimensioned in proximate of budding relationship with the generally flat or horizontal surfaces 93 on the rear stabilizing lands 92 of tooth 14.

As will be readily appreciated by those skilled in the art, the cooperative relationship of the flats 43, 103 and 53, 93 on adapter 12 and tooth 14, respectively, are specifically intended to inhibit any significant movement between the components of the tooth assembly 12 and to promote advantageous transference of forces imparted to the tooth assembly 10 during an excavating operation toward the center line of the tooth assembly 10 and ultimately to the bucket lip 20. Moreover, the cooperative relationship between the stabilizing walls 14, 104 defined by the complementarily disposed stabilizing lands 42, 102 on the adapter 12 and tooth 14, respectively, advantageously facilitate transference of forces imparted to the tooth assembly 10 during an excavating operation. Similarly, and as best shown in FIGURE 1, the stabilizing walls 54 and 94 defined by the complementarily disposed lands 52 and 92 on the adapter 12 and excavating tooth 14, respectively, furthermore aid in the advantageous transference of forces imparted to the tooth assembly 10 during an excavating operation.

When a tooth 14 is to be repaired or replaced, a punch (not shown) is used to drive the fastener 16 through the tooth 14 and out of engagement with the adapter 12. The chamfered or beveled like configuration at opposite ends of the pin 114 of fastener 16 advantageously allows the pin 114 to be driven in either direction and is in effect reversible in operation. Once pin 114

is removed from operable association with insert 112, tooth 14 is removable to allow repair or replacement thereof. When once a repaired/replacement tooth 14 is again fitted about and along the nose portion 23 of the adapter 12, the fastener 16 is reinserted to releasably interconnect the repaired/replacement tooth to the adapter. An advantage to using the type of fastener illustrated in the drawings is that the pin 114 does not have to be orientated in any specific manner for insertion, thus minimizing the chances for improper installation of the fastener 16.

As will be appreciated by those skilled in the art, providing the stabilizing lands 52 toward the rear end of the adapter 12 furthermore enhances accurate locating of the bore 46 relative to the foremost end of the nose portion 23 and relative to the openings 106, 108 in tooth 14 thereby ensuring proper operation of the fastener 16. That is, the flats 53 of the stabilizing lands are disposed generally perpendicular to the vertical axes 48 of bore 46. As such, the flats 53 are disposed to inhibit the tool used to create the bore 46 from dancing along the slanted surface of the adapter, thus enhancing creation of the bore 46.

Another embodiment of an excavating tooth assembly embodying features of the present invention is illustrated in FIGURES 5 and 6. This alternative form of excavating tooth assembly is designated generally by reference numeral 210. The elements of this alternative form of excavating tooth assembly that are identical or functionally analogous to those components discussed above regarding tooth assembly 10 are designated by reference numerals identical to those used above with the exception that this embodiment uses reference numerals in the two hundred series.

In this embodiment of the invention, a lengthwise section of the nose portion 223 of the adapter 212 extends within a cavity 272 defined by the digging tooth 214. Like that discussed

above, the nose portion 223 of the adapter 212 terminates in an end portion 231. The cavity 272 defined by tooth 214 is similarly shaped to that discussed above and includes converging interior slanted surfaces 274 and 276 which diverge angularly and rearwardly from an end wall 218 defined by cavity 272 of tooth 214. Preferably, the end wall 281 of cavity 272 is complimentary to and generally parallels the end region 231 of adapter 212 as shown in FIGURE 6.

In this alternative form of the invention, an elastomeric material is disposed between the adapter 212 and 214 for inhibiting movement there between during the operation of the excavating tooth assembly 210 thereby reducing impact forces between confronting surfaces defined on the adapter 212 and 214.

The elastomeric material disposed between the adapter 212 and excavating tooth 214 is preferably formed from copolymer elastomers such as Hytrel®, an elastomer manufactured by E.I. duPont de Nemours. U.S. Patent Nos. 4,198,037 and 4,566,678 of David G. Anderson and assigned to Miner Enterprises of Geneva, Illinois better describe and disclose particular characteristics of such copolymer elastomers; with the full teachings and disclosure of the above-mentioned anderson patents being incorporated and embodied herein by reference. Suffice it to say, the elastomeric material used in the present invention has a ratio of plastic deformation to its elastic deformation which is greater than 1.5 to 1.

As schematically represented in Figures 5 and 6, an elastomeric member 250 is disposed between the free end 231 of the nose portion 223 of adapter 212 and the terminal wall 281 of cavity 272 defined by tooth 214. The elastomeric member 250 is formed from the same elastomeric material mentioned above. The purpose of the elastomeric member 250 is for absorbing endwise directed impact forces between the tooth 214 and the adapter 212 during

operation of the excavating tooth assembly 210.

Alternatively, and as shown in Figure 7, an elastomeric member 250' can also be disposed between the nose portion 223 of the adapter and the terminal wall 281 of cavity 272 to act as a spring. That is, the member 250' can have a wave-like or rippled configuration between opposite lateral ends thereof and be disposed between the free end 231 of the nose portion 223 of the adapter 212 and the terminal wall 281 of cavity 272 defined on tooth 214. The rippled or sinusoidal configuration of the elastomeric member 250' provides a spring-like effect which augments the locking function of the fastener 216.

Another alternative embodiment of an excavating tooth assembly using elastomeric material between component parts thereof is illustrated in FIGURE 8. This alternative form of excavating tooth assembly is designated generally by reference numeral 310. The elements of this alternative form of excavating tooth assembly that are identical or functionally analogous to those components discussed above regarding tooth assembly 210 illustrated in FIGURES 1 through 4 are designated by reference numerals identical to those used above with the exception that this embodiment uses reference numerals in the three-hundred series.

In this embodiment of the invention, a layer of elastomeric material 350 similar to that disclosed above and having a ratio of plastic deformation to elastic deformation which is greater than 1.5 to 1 is disposed between the exterior slanted upper surface 324 of the nose portion 323 of adapter 312 and the slanted interior surface 374 defined by cavity 372 of tooth 314. Similarly, a layer of elastomeric material 350 of the type having a ration of plastic deformation to elastic deformation which is greater than 1.5 to 1 is disposed between the exterior slanted surface 326 of the nose portion 323 on adapter 312 and the interior slanted surface 376 defined

by cavity 372 in tooth 312.

With this embodiment of the invention, each layer of elastomeric material 350 extends generally the length of the nose portion 323 of adapter 312 and is disposed across the width of those surfaces defined between opposite lateral side edges thereof. As such, elastomeric material disposed along the upper and lower slanted surfaces 324 and 326 and between opposed lateral side edges of the adapter 312 also covers the confronting generally flat surfaces 343 and 303 defined by the stabilizing lands 342 and 302 on adapter 312 and tooth 314 respectively. Moreover, with this embodiment of the invention, elastomeric material 350 is disposed between the confronting generally flat surfaces 353 and 393 defined by the stabilizing lands 352 and 392, respectively, of the adapter 312 and tooth 314. As will be appreciated, the predetermined distances separating the various flat surfaces 343, 303 and 353, 393 of the stabilizing lands 342, 302 and 352, 392, respectively, on the adapter 312 and tooth 314 may require slight modification when elastomeric material is to be arranged therebetween.

In this embodiment of the invention, elastomeric material 350 is also preferably provided between the confronting and generally vertical stabilizing walls 344 and 304 of the forwardly disposed stabilizing lands 342 and 302 on the adapter 312 and tooth 314 respectively. Similarly, elastomeric material 350 is preferably provided between the confronting and generally vertical stabilizing walls 354 and 394 of the rearwardly disposed stabilizing lands 352 and 392 defined between the adapter 312 and tooth 314 respectively. As will be appreciated from an understanding of the present invention, the provision of elastomeric material between the stabilizing walls defined by the fore-and-aft spaced of pairs of stabilizing lands defined on the adapter 312 and tooth 314 substantially reduces, if not eliminates, and tolerance gaps or voids

between the stabilizing walls whereby reducing impact forces therebetween occurring during operation of the excavating tooth assembly 310.

Still another alternative form of the invention using elastomeric material is illustrated in FIGURES 9 and 10. This alternative form of excavating tooth assembly is generally designated by reference numeral 410. The elements of this invention that are the same as or functionally analogous to those components discussed above regarding excavating tooth assembly 10 shown in Figures 1 through 4 are designated by reference numerals identical to those used above with the exception that this embodiment uses reference numerals in the four-hundred series.

In this embodiment of the invention, an elongated and close-ended hollow sleeve 450 of elastomeric material similar to that discussed above and preferably having a ratio plastic deformation to its elastic deformation which is greater than 1.5 to 1 is disposed about and along the nose portion 423 of the adapter 412 before the excavating tooth 414 is arranged in operable combination therewith. As such, and after the excavating tooth 414 is fitted along and about the nose portion 423 of the adapter 412, and as shown in FIGURES 9 and 10, a closed-end 451 of sleeve 450 is entrapped between the free end 431 of the nose portion 423 of adapter 412 and the terminal wall 481 defined by the cavity 472 and the tooth 412.

Similarly, and after tooth 414 is arranged in operable combination with the adapter 412, elastomeric material of sleeve 450 will be entrapped, as shown in FIGURE 9, between confronting slanted interior and exterior surfaces 424, 426 and 474, 476 of the adapter 412 and excavating tooth 414, respectively. Moreover, and after the tooth 414 is fitted along and about and arranged in operable combination with the nose portion 423 of the adapter 412, elastomeric material of sleeve 450 will be entrapped between the sidewalls 428, 430 of the adapter 412 and

the side walls 478, 480 of the cavity 472 defined by tooth 414. As will be appreciated, the dimensioning of the nose portion 423 of adapter 412 and the blind cavity 472 defined by tooth 414 may require slight modification when an elastomeric sleeve such as 450 is fitted along and about the nose portion 423 of the adapter such that a layer of elastomeric material encapsulates the nose portion 423 of the adapter and is disposed between confronting surfaces of the adapter 412 and tooth 414.

The provision of elastomeric material having a ratio of plastic deformation to elastic deformation which is greater than 1.5 to 1 between adjacent and abutting surfaces of the adapter and tooth of multipiece excavating tooth assembly offers significant enhancements over the prior art. For example, the elastomeric material disposed between the nose portion of the adapter and the terminal wall of the cavity defined by the tooth tends to deform in response to horizontal impact forces being exerted on the excavating tooth during an excavating operation. This elastomeric material further serves to augment the locking function of a two piece fastener assembly of the type described above.

In a preferred form of the invention, and to add sufficient strength and rigidity to the components of the multipiece tooth assembly, the adapter and tooth are preferably fabricated in a forging operation. The elastomeric material disposed between adjacent and confronting surfaces readily fills tolerance voids and gaps between the adjacent and confronting surfaces on the forged tooth and adapter thereby significantly and advantageously cushioning impact forces occurring between the adjacent confronting surfaces of the multipiece tooth assembly during an excavating operation. As will be appreciated, reducing impact between adjacent surfaces on the adapter and tooth prolongs usefulness of the multipiece tooth assembly, and, thus, offers

significant economic advantages over the prior art.

From the foregoing, it will be observed that numerous modifications and variations can be effected without departing from the true spirit and scope of the novel concept of the present invention. It will be appreciated that the present disclosure is intended as an exemplification of the invention, and is not intended to limit the invention to the specific embodiment illustrated. The disclosure is intended to cover by the appended claims all such modifications as fall within the scope of the claims.

5

2025-07-15 10:00 AM



**WHAT IS CLAIMED IS:**

1. An excavating tooth assembly comprising:

an adapter having an outer tapered surface configured with a substantially horizontal rearward land section and a substantially horizontal forward land section, said rearward and forward land sections each having a substantially vertical wall configured to facilitate transmission of lateral forces acting on the tooth assembly; and

an excavating tooth configured for attachment to the adapter and having a hollow mounting end defining a cavity configured to mate with the adapter, said hollow mounting end including an inner tapered surface adapted to mate with said outer tapered surface of the adapter, said inner tapered surface configured with a substantially horizontal rearward transmitting section adapted to mate with said rearward land section of the adapter, and a substantially horizontal forward transmitting section adapted to mate with said forward land section of the adapter, said rearward and forward transmitting sections each having a substantially vertical wall configured to mate with the corresponding vertical walls of the rearward and forward land sections to facilitate transmission of lateral forces from the excavating tooth to the adapter.

2. The assembly of claim 1 wherein the vertical walls of the forward land section and the forward transmitting section correspondingly diverge at least partially from a plane normal to the longitudinal centerline of the adapter, and the vertical walls of the rearward land section and the rearward transmitting section correspondingly diverge at least partially from a plane normal to the longitudinal centerline of the adapter, thereby facilitating transmission of lateral forces from the excavating tooth to the adapter.

3. The assembly of claim 2 wherein the vertical walls of the forward land section and the forward transmitting section define the same generally semi-circular shape, and the vertical walls of the rearward land section and the rearward transmitting section define the same generally semi-circular shape.

4. The assembly of claim 1 wherein the forward land section is defined as a recess formed in the outer tapered surface of the adapter and the forward transmitting section protrudes outwardly from the inner tapered surface of the excavating tooth, and wherein the rearward land section protrudes outwardly from the outer tapered surface of the adapter, and the rearward transmitting section is defined as a recess formed in the inner tapered surface of the excavating tooth.

5. The assembly of claim 1 wherein a forward end portion of said nose piece diverges at least partially from a plane normal to the longitudinal centerline of said nose piece, and said cavity in the excavating tooth further comprises a corresponding forward end portion in abutting relationship with the forward end portion of the adapter to facilitate transmission of lateral forces from the excavating tooth to the adapter.

6. The assembly of claim 5 wherein said forward end portion of the adapter is bowed outwardly and the forward end portion of the cavity is a corresponding concave shape for matingly receiving said nose piece.

7. The assembly of claim 1 wherein the rearward land section of the adapter has a bore extending therethrough, and the rearward transmitting section of the tooth has a hole therein to act in conjunction with said bore for the insertion of a fastener therethrough to secure said tooth to said nose piece.

8. The assembly of claim 1 wherein said forward and rearward land sections are formed in an upper, outer tapered surface of the adapter, and said forward and rearward transmitting sections are formed in an upper, inner tapered surface of the excavating tooth, and further comprising corresponding second forward and rearward land sections formed in a lower outer tapered surface of the adapter, and corresponding second forward and rearward transmitting sections formed in a lower inner tapered surface of the excavating tooth.

9. An excavating tooth assembly comprising:

an adapter having an outer tapered surface with a substantially horizontal rearward land section protruding outwardly therefrom and a substantially horizontal forward land section defined as a recess therein, said rearward and forward land sections each having a substantially vertical wall diverging at least partially from a plane normal to the longitudinal centerline of the adapter, thereby facilitating transmission of lateral forces acting on the tooth assembly; and

an excavating tooth attached to the adapter and having a hollow mounting end defining a cavity configured to mate with the adapter, said hollow mounting end including an inner tapered surface adapted to mate with said outer tapered surface of the adapter, said inner tapered surface having a substantially horizontal rearward transmitting section defining a recess

adapted to mate with said rearward land section of the adapter, and a substantially horizontal forward transmitting section protruding therefrom for mating with said forward land section of the adapter, said rearward and forward transmitting sections each having a substantially vertical wall diverging to mate with the corresponding vertical walls of the rearward and forward land sections to facilitate transmission of lateral forces from the excavating tooth the adapter.

10. The assembly of claim 9 wherein the vertical walls of the forward land section and the forward transmitting section define the same generally semi-circular shape, and the vertical walls of the rearward land section and the rearward transmitting section define the same generally semi-circular shape.

11. The assembly of claim 9 wherein a forward end portion of the adapter is bowed outwardly and a forward end portion of the cavity is a corresponding concave shape for matingly receiving said nose piece.

12. The assembly of claim 9 wherein the rearward land section of the adapter has a bore extending therethrough, and the rearward transmitting section of the tooth has a hole therein to act in conjunction with said bore for the insertion of a fastener therethrough to secure said tooth to said nose piece.

13. The assembly of claim 9 wherein said forward and rearward land sections are formed in an upper, outer tapered surface of the adapter, and said forward and rearward

transmitting sections are formed in an upper, inner tapered surface of the excavating tooth, and further comprising corresponding second forward and rearward land sections formed in a lower outer tapered surface of the adapter, and corresponding second forward and rearward transmitting sections formed in a lower inner tapered surface of the excavating tooth.

14. An excavating tooth assembly comprising:

an adapter having an outer tapered surface configured with a substantially horizontal land section through which a bore extends;

an excavating tooth having a cutting end and a hollow mounting end defining a cavity configured to mate with the adapter, said hollow mounting end including an inner tapered surface adapted to mate with said outer tapered surface of the adapter, said inner tapered surface configured with a substantially horizontal transmitting section through which a hole extends to act in conjunction with said bore of the adapter, said transmitting section being configured to mate with the land section of the adapter in abutting relationship to facilitate transmission of vertical forces from the excavating tooth to the adapter; and

a fastener extending through said bore and said hole for securing said excavating tooth to said nose piece.

15. The assembly of claim 14 wherein said land section further comprises a vertical wall diverging at least partially from a plane normal to the longitudinal centerline of said nose piece, and said transmitting section further comprises a corresponding vertical wall in abutting relationship therewith to facilitate transmission of lateral forces from the excavating

tooth to the adapter.

16. The assembly of claim 15 wherein said vertical walls are generally shaped in the form of a semi-circle at least partially surrounding the associated bore and hole.

17. The assembly of claim 14 wherein the land section protrudes outwardly from the outer tapered surface of the adapter, and the transmitting section is defined as a recess formed in the inner tapered surface of the excavating tooth.

18. The assembly of claim 14 wherein a forward end portion of said nose piece diverges at least partially from a plane normal to the longitudinal centerline of said nose piece, and said cavity in the excavating tooth further comprises a corresponding forward end portion in abutting relationship with the forward end portion of the adapter to facilitate transmission of lateral forces from the excavating tooth to the adapter.

19. The assembly of claim 18 wherein said forward end portion of the adapter is bowed outwardly and the forward end portion of the cavity is a corresponding concave shape for matingly receiving said nose piece.

20. The assembly of claim 14 further comprising a substantially horizontal forward land section formed in the outer tapered surface of the adapter and positioned forwardly of said bore, and a substantially horizontal forward transmitting section formed in the inner tapered

surface of the excavating tooth forwardly of said hole, said forward land section and forward transmitting section adapted to mate with each other in abutting relationship to further facilitate transmission of vertical forces from the excavating tooth to the adapter.

21. The assembly of claim 14 wherein said land section is formed in an upper, outer tapered surface of the adapter, and said transmitting section is formed in an upper, inner tapered surface of the excavating tooth, and further comprising a corresponding second land section formed in a lower outer tapered surface of the adapter and through which said bore extends, and a corresponding second transmitting section formed in a lower inner tapered surface of the excavating tooth and through which a second hole extends to act in conjunction with said bore.

22. The assembly of claim 21 further comprising a pair of opposed, substantially horizontal forward land sections formed in corresponding upper and lower outer tapered surfaces of the adapter and positioned forwardly of said bore, and further comprising a pair of opposed, substantially horizontal forward transmitting sections formed in corresponding upper and lower inner tapered surfaces of the excavating tooth forwardly of said hole, said forward land sections and forward transmitting sections adapted to mate with each other in abutting relationship to further facilitate transmission of vertical forces from the excavating tooth to the adapter.

23. An excavating tooth assembly comprising:

an adapter having an outer tapered surface configured with a substantially

horizontal land section protruding outwardly therefrom and through which a bore extends, said land section having a vertical wall diverging at least partially from a plane normal to the longitudinal centerline of said nose piece;

an excavating tooth having a cutting end and a hollow mounting end defining a cavity configured to mate with the adapter, said hollow mounting end including an inner tapered surface adapted to mate with said outer tapered surface of the adapter, said inner tapered surface configured with a recess defining a substantially horizontal transmitting section through which a hole extends to act in conjunction with said bore of the adapter, said transmitting section being configured to mate with the land section of the adapter in abutting relationship to facilitate transmission of vertical forces from the excavating tooth to the adapter, and having a vertical wall corresponding to the vertical wall of the land section to facilitate transmission of lateral forces from the excavating tooth to the adapter; and

a fastener extending through said bore and said hole for securing said excavating tooth to said nose piece.

24. The assembly of claim 23 wherein said vertical walls are generally shaped in the form of a semi-circle at least partially surrounding the associated bore and hole.

25. The assembly of claim 23 wherein a forward end portion of the adapter is bowed outwardly and a forward end portion of the cavity is a corresponding concave shape for matingly receiving said nose piece.



26. The assembly of claim 23 further comprising a substantially horizontal forward land section formed in the outer tapered surface of the adapter and positioned forwardly of said bore, and a substantially horizontal forward transmitting section formed in the inner tapered surface of the excavating tooth forwardly of said hole, said forward land section and forward transmitting section adapted to mate with each other in abutting relationship to further facilitate transmission of vertical forces from the excavating tooth to the adapter.

27. The assembly of claim 24 wherein said land section is formed in an upper, outer tapered surface of the adapter, and said transmitting section is formed in an upper, inner tapered surface of the excavating tooth, and further comprising a corresponding second land section formed in a lower outer tapered surface of the adapter and through which said bore extends, and a corresponding second transmitting section formed in a lower inner tapered surface of the excavating tooth and through which a second hole extends to act in conjunction with said bore.

28. The assembly of claim 24 further comprising a pair of opposed, substantially horizontal forward land sections formed in corresponding upper and lower outer tapered surfaces of the adapter and positioned forwardly of said bore, and further comprising a pair of opposed, substantially horizontal forward transmitting sections formed in corresponding upper and lower inner tapered surfaces of the excavating tooth forwardly of said hole, said forward land sections and forward transmitting sections adapted to mate with each other in abutting relationship to further facilitate transmission of vertical forces from the excavating tooth to the adapter.

29. An assembly for releasably attaching an excavating tooth in a row of teeth to an excavating implement, comprising:

an adapter having a base portion attachable to the excavating implement and a nose portion extending forwardly from said base portion, said nose portion having laterally spaced sides and converging upper and lower surfaces terminating at a forward end, with the base portion of the adapter defining an elongated aperture open at opposite ends, and with the upper and lower surfaces defining, in combination, at least three generally parallel support surfaces, each support surface opening to the forward end of the adapter surrounded by a generally vertical stabilizing surface extending normal to and between the support surface and the respective upper or lower surface of the adapter, with each stabilizing surface having a lateral width less than the lateral spacing between the sides of the nose portion of said adapter;

an excavating tooth defining a blind cavity configured to snugly fit endwise about the nose portion of the adapter, with the blind cavity defined by said tooth having upper and lower surfaces that complement the upper and lower surfaces of said nose portion of the adapter and include structure for abutting and cooperating with the three support surfaces on the adapter, and wherein the stabilizing surface surrounding each support surface of the adapter being adapted to abut in mating relationship with said structure on said tooth to transfer side load forces imparted to the tooth toward a centerline of the adapter, said tooth further defining a pair of axially aligned openings that open to the cavity in the tooth; and

pin structure extendable through the openings in the tooth and through the aperture in said adapter to releasably hold the tooth to the adapter.

30. An assembly for attaching an earth engaging tooth to a ground engaging implement, comprising:

a support having a base attachable to the implement and a nose extending forwardly from said base, said nose having laterally spaced sides and converging upper and lower surfaces terminating at a forward end, said base of the support defining an elongated aperture open at opposite ends, and with the upper and lower surfaces defining, in combination, at least three generally parallel support surfaces, each support surface opening to the forward end of the support and is surrounded by a generally stabilizing surface extending normal to and between the support surface and the respective upper or lower surface of the support;

said tooth having upper and lower surfaces that complement the upper and lower surface of said nose of the support and include structure for abutting and cooperating with the three support surfaces on the support, and wherein the stabilizing surface surrounding each support surface of the support being adapted to abut in mating relationship with said structure on said tooth, said tooth further defining a pair of axially aligned openings that open to the cavity in the tooth; and

pin structure extendable through the openings in the tooth and through the aperture in said support to releasably hold the tooth to the support.

31. An assembly for attaching a ground engaging tooth to a ground engaging implement comprising:

a support attachable at a rear end to the implement and having a nose extending forwardly to a free terminal end, said nose having laterally spaced and opposed sides and upper

and lower surfaces converging toward the terminal end of said support, said support further defining an opening extending through the support toward the rear end thereof and which is open at opposite ends, said upper and lower surfaces each defining a pair of fore-and-aft spaced support surfaces, with each support surface having a lateral width less than the distance between said sides and opening to the terminal end of said support , each support surface includes a stabilizing surface extending in surrounding and normal relation relative to and between the support surface and the respective upper and lower surfaces of the support;

said tooth defining a blind cavity configured to snugly fit endwise about the nose of the adapter and including upper and lower surfaces that complement the upper and lower surfaces on the nose of the support, with the upper and lower surfaces of the blind cavity each including first and second structures for abutting and cooperating with the pairs of support surfaces on the upper and lower surfaces of the support, with the stabilizing surface of each support surface on the support being adapted to abut in mating relationship with structures on the tooth to transfer side loads imparted to the tooth to the center of the support, said tooth further defining a pair of openings arranged along a centerline passing through the blind cavity in the tooth; and

pin structure extendable through the openings in the tooth and the aperture in said support for attaching said tooth to said support.

32. An assembly for attaching a ground engaging tooth to a ground engaging implement, comprising: a support attachable at a rear end to the implement and having a nose extending forwardly to a free terminal end with a forwardly projecting curvilinear configuration,

269260 506880  
said nose having laterally spaced and opposed sides and upper and lower surfaces converging toward the terminal end of said support, said support further defining an opening extending through the support toward the rear end thereof and which is open at opposite ends, said upper and lower surfaces each defining first and second fore-and-aft spaced and vertically aligned support surfaces, with each support surface having a lateral width less than the distance between said sides, with the first support surface on the upper and lower surfaces of the support extending rearwardly from an d opening to the terminal end of said support and with the second support surface on the upper and lower surfaces of the support being disposed toward the rear end of the support, each support surface including a stabilizing surface extending in surrounding and normal relation relative to and between the support surface and the respective upper and lower surfaces of the support;

said tooth defining a blind cavity configured to snugly fit endwise about the nose of the adapter and including upper and lower surfaces that complement the upper and lower surfaces on the nose of the support, wherein the blind cavity of the tooth defines a curvilinear surface that is a mirror image of the curvilinear surface of the terminal end of said support such that the tooth is subject to self-centering in response to horizontal loads being applied thereto, and with the upper and lower surface of the blind cavity each including first and second structures for abutting and cooperating with the first and second support surfaces on the upper and lower surfaces of the support, and wherein the stabilizing surface of each support surface on the support being adapted to abut in mating relationship with the structures on the tooth to transfer side loads imparted to the tooth to the center of the support, said tooth further defining a pair of openings arranged along a centerline passing through the blind cavity in the tooth; and

pin structure extendable through the openings in the tooth and the aperture in said support for attaching said tooth to said support.

33. An excavating tooth assembly, comprising:

an adapter having a base portion configured for attachment to excavating equipment and a nose portion integrally formed with and extending from said base portion;

an elongated excavating tooth having a cutting edge toward one end thereof and a blind cavity opening to an opposite end thereof, said blind cavity being configured to snugly fit about and along a lengthwise portion of the nose portion of said adapter; and

an elastomeric member disposed between a free end of said nose portion on said adapter and a terminal wall of said blind cavity on said tooth for absorbing endwise directed impact forces between said tooth and said adapter incurred during operation of said excavating tooth assembly.

34. The excavating tooth assembly according to Claim 33 wherein said elastomeric member is formed from an elastomeric material having a ratio of plastic deformation to elastic deformation which is greater than 1.5 to 1.

35. A multipiece excavating tooth assembly, comprising:

an excavating tooth adapted for releasable association along and about a lengthwise portion of an adapter, and wherein a elongated pin passing through said adapter and operably associated with said tooth maintains said tooth in operable association with said adapter;

and

elastomeric material having a ratio of plastic deformation to elastic deformation greater than 1.5 to 1 is disposed between the tooth and the adapter for inhibiting movement therebetween during operation of the excavating tooth assembly thereby reducing impact forces between adjacent confronting surfaces defined on said adapter and said tooth.

36. The excavating tooth assembly according to Claim 35 wherein said adapter includes a nose portion configured with upper and lower slanting surfaces converging toward a free end of the adapter, and wherein said excavating tooth defines a blind cavity opening to a rear end thereof, said blind cavity having a configuration generally corresponding to the configuration of the nose portion of said adapter.

37. The excavating tooth assembly according to Claim 35 wherein said elastomeric material is formed as an elongated sleeve which fits over and along the nose portion of said adapter such that an layer of elastomeric material is disposed between confronting surfaces defined on the nose portion of the adapter and blind cavity defined by said excavating tooth after the excavating tooth is assembled to the adapter.

38. The excavating tooth assembly according to Claim 36 wherein the nose portion of the adapter and the blind cavity defined by said tooth each include stabilizing lands disposed thereon in cooperative relationship relative to each other to stabilize operation of the tooth assembly during an excavating operation.

39. The excavating tooth assembly according to Claim 38 wherein said stabilizing land comprises a pair of generally horizontal surfaces defined on said adapter and said tooth in confronting relationship relative to each other, and wherein said elastomeric material is disposed between the horizontal surfaces to cushion movements therebetween.

40. The excavating tooth assembly according to Claim 36 wherein the nose portion of the adapter and the blind cavity defined by said tooth each include fore-and- aft spaced pairs of stabilizing lands disposed thereon in cooperative relationship relative to each other to stabilize operation of the tooth assembly during an excavating operation.

41. The excavating tooth assembly according to Claim 38 wherein each pair of stabilizing lands comprises a pair of generally horizontal surfaces defined on said adapter and said tooth in confronting relationship relative to each other, and wherein said elastomeric material is disposed between the horizontal surfaces to cushion movements therebetween.

42. A multipiece excavating tooth assembly, comprising:

- an adapter having a base portion configured for attachment to excavating equipment and a nose portion extending from said base portion;
- an elongated excavating tooth having front edge toward one end thereof and a blind cavity opening to a rear end thereof, said blind cavity being configured to snugly fit about and along a lengthwise portion of the nose portion of said adapter;
- an elongated pin for releasably locking the tooth to said adapter, said pin passing



endwise through said adapter into operable association with said tooth, and wherein said pin is resiliently biased into position to releasably lock said tooth to said adapter; and

a spring disposed between said adapter and said tooth for augmenting the locking function of said pin.

43. The multipiece excavating tooth assembly according to Claim 42 wherein said spring is operably disposed between said nose portion of said adapter and a terminal wall of the blind cavity defined by said tooth.

44. The multipiece excavating tooth assembly according to Claim 42 wherein said spring is formed from elastomeric material having a ratio of plastic deformation to plastic deformation greater than 1.5 to 1.

45. The multipiece excavating tooth assembly according to Claim 44 wherein said elastomeric material has a sinusoidal configuration between opposite lateral ends thereof.

46. The multipiece excavating tooth assembly according to Claim 44 wherein said elastomeric material has a rippled configuration between opposite lateral ends thereof for facilitating compression and expansion of said spring in response to forces acting thereon.

47. The multipiece excavating tooth assembly according to Claim 42 wherein elastomeric material is disposed between the nose portion of said adapter and opposed walls

defined by said blind cavity of said tooth for absorbing impact forces occurring therebetween during operation of the excavating tooth assembly.

48. The multipiece excavating tooth assembly according to Claim 42 wherein said nose portion of the adapter and opposed walls defined by the blind cavity of said tooth combine to define stabilizing lands for inhibiting movement between the tooth and the adapter during operation of the excavating tooth assembly.

49. The multipiece excavating tooth assembly according to Claim 48 wherein elastomeric material having a ratio of plastic deformation to elastic deformation greater than 1.5 to 1 is disposed between the stabilizing lands on said adapter and said tooth.

50. The multipiece excavating tooth assembly according to Claim 48 wherein the stabilizing lands include generally flat horizontal surfaces arranged in confronting relation relative to each other for inhibiting movement between said tooth and the adapter during an excavating operation of the tooth assembly.

51. The multipiece excavating tooth assembly according to Claim 48 wherein each stabilizing land further includes generally vertical walls depending from the generally flat surfaces, and wherein the vertical wall on the stabilizing land defined by said adapter and the vertical wall defined by the stabilizing land on said tooth are arranged in confronting relation relative to each other when the tooth is arranged in operable combination with the adapter.

52. The multipiece excavating tooth assembly according to Claim 51 wherein elastomeric material is disposed between the confronting vertical walls of the stabilizing lands when the tooth is arranged in operable combination with the adapter.

53. The multipiece excavating tooth assembly according to Claim 52 wherein said elastomeric material has a ratio of plastic deformation to elastic deformation greater than 1.5 to 1.

54. An excavating tooth assembly for ground engaging equipment, comprising:

- a support attachable at a rear end to the equipment and having a nose extending forwardly to a free terminal end, said nose having laterally spaced and opposed sides and upper and lower surfaces converging toward the terminal end of said support, said support further defining an opening extending through the support toward the rear end thereof and which is open at opposite ends;
- an excavating tooth defining a blind cavity opening to a rear end of said tooth and configured to snugly fit endwise about and along the nose of the support and including upper and lower surfaces that complement the upper and lower surfaces on the nose of the support, said tooth further defining a pair of generally aligned openings which open to the blind cavity in the tooth;
- a fastener extendable through the openings in the tooth and the aperture in said support for releasably locking said tooth to said support; and
- elastomeric material having a ratio of plastic deformation to elastic deformation

greater than 1.5 to 1 disposed between the upper and lower surfaces defined by said support and said tooth.

55. The multipiece excavating tooth assembly according to Claim 54 wherein the nose of said adapter and opposed walls defined by the blind cavity of said tooth combine to define stabilizing lands for inhibiting movement between the tooth and the adapter during operation of the excavating tooth assembly.

56. The multipiece excavating tooth assembly according to Claim 54 wherein said elastomeric material is disposed between the stabilizing lands on said adapter and said tooth.

57. The multipiece excavating tooth assembly according to Claim 54 wherein the stabilizing lands include generally flat horizontal surfaces arranged in confronting relation relative to each other for inhibiting movement between said tooth and the adapter during an excavating operation of the tooth assembly.

58. The multipiece excavating tooth assembly according to Claim 57 wherein each stabilizing land further includes generally vertical walls depending from the generally flat surfaces, and wherein the vertical wall on the stabilizing land defined by said adapter and the vertical wall defined by the stabilizing land on said tooth are arranged in confronting relation relative to each other when the tooth is arranged in operable combination with the adapter.

59. The multipiece excavating tooth assembly according to Claim 58 wherein elastomeric material is disposed between the confronting vertical walls of the stabilizing lands when the tooth is arranged in operable combination with the adapter.

60. The multipiece excavating tooth assembly according to Claim 54 wherein said fastener includes a locking member biased into releasable locking engagement with a retaining pin for holding said pin against movement during operation of said excavating tooth assembly.

61. The multipiece excavating tooth assembly according to Claim 59 further including a spring disposed between said adapter and said tooth for augmenting the locking function of said fastener.

62. The multipiece excavating tooth assembly according to Claim 61 wherein said spring comprises a elastomeric member disposed between the free end of the nose on said adapter and the terminal wall of the blind cavity defined by said tooth.

63. A multipiece excavating tooth assembly, comprising:  
an adapter having a base portion attachable to excavating equipment and a nose portion extending forwardly from said base portion, said nose portion having a series of exterior surfaces including laterally spaced side surfaces and upper and lower surfaces terminating at a forward end, with the base portion of the adapter defining an elongated aperture open at opposite ends;

an excavating tooth defining a blind cavity opening to a rear end of said tooth, said blind cavity being configured to snugly fit endwise along and about the nose portion of the adapter, with the blind cavity defined by said tooth having a series of interior surfaces including upper and lower surfaces configured to complement the upper and lower surfaces of said nose portion of the adapter, said tooth further defining a pair of openings arranged along a centerline passing through the blind cavity in the tooth;


a fastener extendable through the openings in the tooth and through the aperture in said adapter to releasably hold the tooth to the adapter; and

a sleeve adapted to fit along and about the nose portion of said adapter in surrounding relation thereto and between the exterior surfaces of said adapter and the interior surfaces of the blind cavity defined by said tooth for blunting impact forces therebetween incurred during operation of said excavating tooth assembly, and wherein said sleeve is fabricated from an elastomeric material having a ratio of plastic deformation to elastic deformation greater than 1.5 to 1.


### ABSTRACT OF THE DISCLOSURE

A multipiece excavating tooth assembly including an adapter and an excavating tooth. A fastener releasably interconnects and maintains the excavating tooth in operable combination with the adapter. When assembled, an elongated nose portion of the adapter extends into a blind cavity defined by and which opens to a rear end of the excavating tooth. According to one aspect of the invention, the adapter and tooth define a pair of fore-and-aft spaced stabilizing lands for advantageously transferring impact forces imparted to the tooth assembly during an excavating operation. Each stabilizing land on the tooth assembly is comprised of a pair of generally horizontal flats arranged in confronting relation relative to each other when the excavating tooth is arranged in operable combination with the adapter. Further includes a generally vertical stabilizing wall arranged in depending relation relative to the flat. According to another aspect of the present invention elastomeric material is disposed between the adapter and the excavating tooth for absorbing impact forces imparted therebetween.


08938409.092637









08938909, 092697



1990-1991		1991-1992		1992-1993		1993-1994		1994-1995		1995-1996		1996-1997		1997-1998		1998-1999		1999-2000		2000-2001		2001-2002		2002-2003		2003-2004		2004-2005		2005-2006		2006-2007		2007-2008		2008-2009		2009-2010		2010-2011		2011-2012		2012-2013		2013-2014		2014-2015		2015-2016		2016-2017		2017-2018		2018-2019		2019-2020		2020-2021		2021-2022		2022-2023		2023-2024		2024-2025		2025-2026		2026-2027		2027-2028		2028-2029		2029-2030		2030-2031		2031-2032		2032-2033		2033-2034		2034-2035		2035-2036		2036-2037		2037-2038		2038-2039		2039-2040		2040-2041		2041-2042		2042-2043		2043-2044		2044-2045		2045-2046		2046-2047		2047-2048		2048-2049		2049-2050		2050-2051		2051-2052		2052-2053		2053-2054		2054-2055		2055-2056		2056-2057		2057-2058		2058-2059		2059-2060		2060-2061		2061-2062		2062-2063		2063-2064		2064-2065		2065-2066		2066-2067		2067-2068		2068-2069		2069-2070		2070-2071		2071-2072		2072-2073		2073-2074		2074-2075		2075-2076		2076-2077		2077-2078		2078-2079		2079-2080		2080-2081		2081-2082		2082-2083		2083-2084		2084-2085		2085-2086		2086-2087		2087-2088		2088-2089		2089-2090		2090-2091		2091-2092		2092-2093		2093-2094		2094-2095		2095-2096		2096-2097		2097-2098		2098-2099		2099-2100		2100-2101		2101-2102		2102-2103		2103-2104		2104-2105		2105-2106		2106-2107		2107-2108		2108-2109		2109-2110		2110-2111		2111-2112		2112-2113		2113-2114		2114-2115		2115-2116		2116-2117		2117-2118		2118-2119		2119-2120		2120-2121		2121-2122		2122-2123		2123-2124		2124-2125		2125-2126		2126-2127		2127-2128		2128-2129		2129-2130		2130-2131		2131-2132		2132-2133		2133-2134		2134-2135		2135-2136		2136-2137		2137-2138		2138-2139		2139-2140		2140-2141		2141-2142		2142-2143		2143-2144		2144-2145		2145-2146		2146-2147		2147-2148		2148-2149		2149-2150		2150-2151		2151-2152		2152-2153		2153-2154		2154-2155		2155-2156		2156-2157		2157-2158		2158-2159		2159-2160		2160-2161		2161-2162		2162-2163		2163-2164		2164-2165		2165-2166		2166-2167		2167-2168		2168-2169		2169-2170		2170-2171		2171-2172		2172-2173		2173-2174		2174-2175		2175-2176		2176-2177		2177-2178		2178-2179		2179-2180		2180-2181		2181-2182		2182-2183		2183-2184		2184-2185		2185-2186		2186-2187		2187-2188		2188-2189		2189-2190		2190-2191		2191-2192		2192-2193		2193-2194		2194-2195		2195-2196		2196-2197		2197-2198		2198-2199		2199-2200		2200-2201		2201-2202		2202-2203		2203-2204		2204-2205		2205-2206		2206-2207		2207-2208		2208-2209		2209-2210		2210-2211		2211-2212		2212-2213		2213-2214		2214-2215		2215-2216		2216-2217	
-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--	-----------	--







08938909.092697






FIG. 7






08938909, 092697



08938909 .092597



**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY  
STATUS (37 CFR 1.9(f) AND 1.27 (b)) - INDEPENDENT INVENTOR**

Docket No.  
30495.00.017

Serial No.  
Unknown

Filing Date  
Herewith

Patent No.

Issue Date

Applicant/ **Brian L. Launder; Charles Clendenning**  
Patentee:

Invention: **EXCAVATING TOOTH ASSEMBLY**

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled above and described in:

- ☐ the specification to be filed herewith.  
☒ the application identified above.  
☐ the patent identified above.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☐ No such person, concern or organization exists.  
☒ Each such person, concern or organization is listed below.

\*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities (37 CFR 1.27)

FULL NAME **H & L Tooth Company**

ADDRESS **10055 East 56th St. North, Tulsa, Oklahoma 74117-4016**
☐ Individual ☒ Small Business Concern ☐ Nonprofit Organization

FULL NAME

ADDRESS

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

FULL NAME

ADDRESS

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

FULL NAME

ADDRESS

☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF INVENTOR Brian L. Launder

SIGNATURE OF INVENTOR 

DATE: Aug 29 1997

NAME OF INVENTOR Charles Clendenning

SIGNATURE OF INVENTOR 

DATE: 8-29-97

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

NAME OF INVENTOR \_\_\_\_\_

SIGNATURE OF INVENTOR \_\_\_\_\_

DATE: \_\_\_\_\_

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY  
STATUS (37 CFR 1.9(f) AND 1.27 (c)) - SMALL BUSINESS CONCERN**

Docket No.  
30495.00.017

Serial No.  
UNKNOWN

Filing Date  
HEREWITH

Patent No.

Issue Date

Applicant/ **Brian L. Launder; Charles Clendenning**  
Patentee:

Invention: **EXCAVATING TOOTH ASSEMBLY**

I hereby declare that I am:

- ☐ the owner of the small business concern identified below:
- ☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN: **H&L Tooth Company**

ADDRESS OF CONCERN: **10055 East 56th Street North; Tulsa, Oklahoma 74117-4016**

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under Section 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the above identified invention described in:

- ☐ the specification filed herewith with title as listed above.
- ☒ the application identified above.
- ☐ the patent identified above.

If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed on the next page and no rights to the invention are held by any person, other than the inventor, who could not qualify as an independent inventor under 37 CFR 1.9(c) or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

20250310 10:36:30

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ no such person, concern or organization exists.  
☐ each such person, concern or organization is listed below.

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

FULL NAME

ADDRESS

☐

Individual

☐

Small Business Concern

☐

Nonprofit Organization

Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING:


Brian L. Launder

TITLE OF PERSON SIGNING

OTHER THAN OWNER:

ADDRESS OF PERSON SIGNING:

SIGNATURE:



DATE:

Aug 29 1997

Docket No.  
30495.00.017

# Declaration and Power of Attorney For Patent Application

## English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

**EXCAVATING TOOTH ASSEMBLY**

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on \_\_\_\_\_ as United States Application No. or PCT International Application Number \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

None

(Number)

(Country)

(Day/Month/Year Filed)

☐

(Number)

(Country)

(Day/Month/Year Filed)

☐

(Number)

(Country)

(Day/Month/Year Filed)

☐

I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

None	
(Application Serial No.)	(Filing Date)
(Application Serial No.)	(Filing Date)
(Application Serial No.)	(Filing Date)

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112. I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

None		
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. *(list name and registration number)*

**Mark I. Feldman (Reg. No. 26,880)**

**John W. Harbst (Reg. No. 28,018)**

**Gary L. Hermanson (Reg. No. 34,349)**


**William T. Rifkin (Reg. No. 26, 501)**


**James P. Ryther (Reg. No. 20,424)**

**Mary S. Burns (Reg. No. 32,116)**

Send Correspondence to: **John W. Harbst**  
**RUDNICK & WOLFE**  
**203 North LaSalle Street**  
**Chicago, IL 60601-1293**

Direct Telephone Calls to: *(name and telephone number)*  
**John W. Harbst - (312) 368-8930**

Full name of sole or first inventor <b>Brian L. Launder</b>	
Sole or first inventor's signature 	Date <i>Aug 29 1997</i>
Residence <b>10055 E. 56th St. North, Tulsa, Oklahoma 74117-4016</b>	
Citizenship <b>United States of America</b>	
Post Office Address <b>Same</b>	

Full name of second inventor, if any <b>Charles Clendening</b>	
Second inventor's signature 	Date <i>8-29-97</i>
Residence <b>7514 Bushnell Blvd., Broken Arrow, Oklahoma 74014</b>	
Citizenship <b>United States of America</b>	
Post Office Address <b>Same</b>	